



TANK VARIANTS

CAPACITY (Litres)	RAIL WIDTH	HOOK HEIGHT (1050 - 1570)	TARE WEIGHT	LENGTH (A)	WIDTH	HEIGHT (B)
11,000	1060	ADJUSTABLE	1,895	6,100	2,480	2,520
13,000	1060	ADJUSTABLE	2,065	6,400	2,480	2,580
15,000	1060	ADJUSTABLE	2,180	6,400	2,480	2,805

TANK

MATERIAL	Marine Grade 5083 Aluminium
MAX. CAPACITY	As per Customer Preference
BAFFLE SYSTEM	Ball-Baffle System, Bbs Tested & Approved By Loadsafe Australia 1 Ball Every 40 Litres
TANK FEATURES	Lightweight, Increased Payload Translucent Food Grade Poly Corrosion Resistant Flex And Impact Resistant 15-Year Tank Warranty Heavy Duty Pin Mounts Low Profile Tank Design Water Level Sight Gauge Pressure Relief Valve

WATER PUMP AND DRIVE SYSTEM

MODEL	Heavy Duty Self Priming GMP Pump
PERFORMANCE	1800 LPM @ 65 PSI with 46 Metre Head
ENGINE	Honda Petrol 13HP Electric Start Engine
COUPLING	Direct Coupled Mechanical Drive

ELECTRICAL SYSTEM

HARNESS AND WIRING	Marine Grade MDG15 Harness Compliant Braiding
CONTROLS	Individually Programmed Remote Control
POWER	Battery with Individual Battery Lockout Isolator
LIGHTING	Hella LED Lights 1 x Rear Beacon

WATER SPRAY SYSTEM

BATTERY SPRAYS	2 x 80mm (2") Left And Right Rear 1 x 80mm (2") Center Rear
HOSE REEL	Heavy Duty Spring Rewind Hose Reel Down Hose With Fire Fighting Nuzzle
OUTLETS	1 x 50mm (3") Pump Outlet 1 x Garden Tap Outlet
TANK-FILL	1 x 80mm (3) Pump with One-Way Swing Check Valve 1 x Large Overhead Fill Funnel
ACTUATORS	Electric Over Air With Spring Return Close Valves | Air Connection Required From Truck Chassis

COMPLIANCE CERTIFICATIONS: Back-Flow Certification AND Risk Assessment are completed as part of the Allquip's quality assurance. For a wide range of options, contact our Allquip sales team.