



TRAILER SPECS

MODEL	PT-22000 Semi Trailer
CHASSIS	Fully Fabricated 16mm Top Flange & 20mm Bottom Flange
SKID PLATE	10mm Skid Plate Single Position Fixed
TOWING EYE	50mm King Pin
AXLES	2 x FUWA Hitch 20" Drum Brakes 10/285 PCD Long Studs
SUSPENSION	FUWA K Hitch 1232mm Bogie-Axle Overslung Spring 9 Leaf
RIDE HEIGHT	385mm
OUTER RIMS	4 x 22.5" x 8.25" 10 Stud Steel 285 PCD
INNER RIMS	5 x 22.5" x 8.25" 10 Stud Steel 285 PCD

TYRES	9 x 275/70R x 22.5"
MUDGUARD	2 x Conveyer Rubber Guards
COATING	Fully Sandblasted with Polyzinc Undercoat & Powder Coat Topcoat
COLOR	Black
LIGHTS	LED Hella Trailer Light Kit
TOOLBOX	1200mm x 450mm x 380mm
SPARE WHEEL	Semi Trailer Swing Type
LANDING LEGS	FUWA K Hitch 2 Speed
COUPLING	Off-Road Recovery Coupling

TANK

MATERIAL	UV - Stabilised Polyethylene Also available in Aluminium
MAX. CAPACITY	2 x 11000L Polyethylene Tanks
BAFFLE SYSTEM	Ball-Baffle System, BBS Tested and Approved by Loadsafe Australia 1 Ball Every 40 Litres
TANK FEATURES	Lightweight, Increased Payload Translucent Food Grade Poly Corrosion Resistant Flexible and Impact Resistant 15-Year Tank Warranty Heavy Duty PIN Mounts Low Profile Tank Design Water Level Sight Gauge Pressure Relief Valve

ELECTRICAL SYSTEM

HARNESS AND WIRING	Marine Grade MDG15 Harness Compliant Braiding
CONTROLS	Individually Programmed 16 Channel Remote Control
POWER	850 CCA Battery with Individual Battery Lockout Isolator
LIGHTING	Hella LED Lights 2 x Front and Rear Beacon

WATER SPRAY SYSTEM

BATTERY SPRAYS	2 x 80mm (3") Left And Right Rear 1 x 80mm (3") Center Rear
SPRAY BAR	Pressure Fed V-Jet Bar With 14 Brass V-Jet Nozzles With End Caps
HOSE REEL	Heavy Duty Spring Manual Rewind Hose Reel
OUTLETS	1 x 80mm (3") Pump Outlet 1 x Garden Tap Outlet
TANK-FILL	1 x 80mm (3) Pump with One-Way Swing Check Valve
ACTUATORS	Electric Over Air with Spring Return Close Valves Air Connection Required

WATER PUMP AND DRIVE SYSTEM

MODEL	Heavy Duty Self Priming GMP Pump
PERFORMANCE	2,300 LPM @ 46 PSI with 32 Metre Head
ENGINE	Kohler Diesel 19HP Electric Start Engine
DRIVE SYSTEM	Flexible Type Coupling Drive



TRAILER DIMENSIONS

CAPACITY	WHEELBASE	GVM	TARE WEIGHT	LENGTH	WIDTH	HEIGHT
16,500 litres	6,380 mm	28,000	6,940 kg	9,480 mm	2,490 mm	3,530 mm





TRAILER SPECS

MODEL	PT-28000 Trailer
CHASSIS	Fully Fabricated 16mm Top Flange & 20mm Bottom Flange
SKID PLATE	10mm Skid Plate Single Position Fixed
TOWING EYE	50mm King Pin
AXLES	3 x FUWA Hitch 20" Drum Brakes 10/285 PCD Long Studs
SUSPENSION	FUWA K Hitch 1232mm Bogie-Axle Overslung Spring 9 Leaf
RIDE HEIGHT	385mm
OUTER RIMS	6 x 22.5" x 8.25" 10 Stud Steel 285 PCD
INNER RIMS	7 x 22.5" x 8.25" 10 Stud Steel 285 PCD

TYRES	13 x 275/70R x 22.5"
MUDGUARD	3 x Conveyer Rubber Guards
COATING	Fully Sandblasted with Polyzinc Undercoat & Powder Coat Topcoat
COLOR	Black
LIGHTS	LED Hella Trailer Light Kit
TOOLBOX	1200mm x 450mm x 380mm
SPARE WHEEL	Semi Trailer Swing Type
LANDING LEGS	FUWA K Hitch 2 Speed
COUPLING	Off-Road Recovery Coupling

TANK

MATERIAL	UV - Stabilised Polyethylene Also available in Aluminium
MAX. CAPACITY	2 x 13000L Polyethylene Tanks
BAFFLE SYSTEM	Ball-Baffle System, BBS Tested and Approved by Loadsafe Australia 1 Ball Every 40 Litres
TANK FEATURES	Lightweight, Increased Payload Translucent Food Grade Poly Corrosion Resistant Flexible and Impact Resistant 15-Year Tank Warranty Heavy Duty PIN Mounts Low Profile Tank Design Water Level Sight Gauge Pressure Relief Valve

WATER PUMP AND DRIVE SYSTEM

MODEL	Heavy Duty Self Priming GMP Pump
PERFORMANCE	2,300 LPM @ 46 PSI with 32 Metre Head
ENGINE	Kohler Diesel 19HP Electric Start Engine
DRIVE SYSTEM	Flexible Type Coupling Drive

ELECTRICAL SYSTEM

HARNESS AND WIRING	Marine Grade MDG15 Harness Compliant Braiding
CONTROLS	Individually Programmed 16 Channel Remote Control
POWER	850 CCA Battery with Individual Battery Lockout Isolator
LIGHTING	Hella LED Lights 2 x Front and Rear Beacon

WATER SPRAY SYSTEM

BATTERY SPRAYS	2 x 80mm (3") Left And Right Rear 1 x 80mm (3") Center Rear
SPRAY BAR	Pressure Fed V-Jet Bar With 14 Brass V-Jet Nozzles With End Caps
HOSE REEL	Heavy Duty Spring Manual Rewind Hose Reel
OUTLETS	1 x 80mm (3") Pump Outlet 1 x Garden Tap Outlet
TANK-FILL	1 x 80mm (3) Pump with One-Way Swing Check Value
ACTUATORS	Electric Over Air with Spring Return Close Valves Air Connection Required

TRAILER DIMENSIONS

CAPACITY	WHEELBASE	GVM	TARE WEIGHT	LENGTH	WIDTH	HEIGHT
26,000 litres	6,740 mm	32,000	7,860 kg	10,010 mm	2,490 mm	3,875 mm